

Article no.: 300500, 300505, 300510

Description

Hanseline – CHAIN LUBE Grease is natural colored, lithium saponated grease of the consistency NLGI grade 0 based on mineral oils. Strong points are low starting resistance at low temperatures, squeeze-stable, very good water resistance and high corrosion protection.



Usage

Hanseline – CHAIN LUBE Grease lubricates fast running drive chains, also suited for filling gearboxes of spur-, bevel- and worm gear systems. Especially suited for long-term lubrication by high-pressure resistance.

Hint: For easy usage set the tube in a glass of hot water and heat up to app. 45°C, makes the grease highly fluid and thus helps creeping to the lubricating point. Hang the tube head first at the clip, so the grease flows to the spout – not to the bottom.

Technical Data

| | |
|---|---------------------------------------|
| appearance: | paste |
| color: | natural (yellow-brown) |
| odour: | neutral |
| Service temperature: | -30 to +100°C (permanent lubrication) |
| Melting point (DIN ISO 2176): | ca. 180°C |
| Penetration (DIN ISO 2137): | 355 to 385 |
| Water sustainability (DIN 51 807 T1): | 1 - 90 |
| Corrosion protection (DIN 51802): | corrosion category 0 |
| Viscosity of base oil at 40°C (DIN 51 562): | ca. 100 mm ² /s |

Specifications are subject to change without notice! All information provided was researched and processed to the best of our knowledge, liability excluded. For further information contact our technical service.

TARIC

2710 19 99

Packaging



50ml

Inner-
cartons of 10 in
outer carton of 100



250ml; 1000ml
carton of 12

(incl. German VAT) recommended retail price € 2,95 / 50ml